



PULASTIC® ELITE LINE

WOODEN SUBFLOOR SYSTEMS
PROVIDING OUTSTANDING COMFORT
& SAFETY FOR AREA- AND COMBI-
ELASTIC SPORTS FLOORS

PULASTIC®
SPORTS FLOORING

A SIKA BRAND

WOODEN SUBFLOOR SYSTEMS PROVIDING OUTSTANDING COMFORT & SAFETY FOR AREA- AND COMBI-ELASTIC SPORTS FLOORS



GREAT PERFORMANCE

The Pulastic® Elite range has been designed to provide the ultimate level in safety and comfort in Pulastic® sports flooring. In the Pulastic® Elite range you will find a perfect basis for a combination of all point-elastic Pulastic® sports floors with the area-elastic subfloors of this range.

THE ADVANTAGES OF THE PULASTIC® ELITE LINE

- Ultimate level in safety and comfort.
- Excellent long term resiliency for comfort and injury prevention.
- Outstanding load bearing capacity and impact resistance.
- Low total cost of ownership.
- Very suitable for installation of floor heating and thermal insulation.
- Wide range of toplayer finishes available, ranging from 2 mm to 9 mm, offering area- or combi-elastic characteristics.
- Outstanding noise reduction (acoustic isolation) up to 29 dB.
- Sustainable through renewable raw materials.
- All wood products used are FSC labelled.
- Sika Netherlands is VCA** certified for job site safety, and works according to the Responsible Care/EQHS management system BS OHSAS 18001.
- Pulastic® sport floors are manufactured under ISO 9001 for quality management, ISO 14001 for environmental care. Sika Netherlands is a Level 3 certified company according to the CSR Performance Ladder. These standards are inspired by ISO 26000 for corporate sustainability.

CHOOSING THE RIGHT FLOOR


All the floors of the Pulastic Elite range excel in comfort because of their resiliency. This will in any case help reduce fatigue and prevent injuries. And by choosing a floor system with the required need for load bearing capacity and impact resistance, the subfloors from the Elite range will contribute to a floor that will fit all your high level demands.

WOOD WITH A SEAMLESS CONSTRUCTION

The Pulastic® Elite line is composed as follows:

- A special prefabricated shockpad in different grades or a so called wooden bar and rebar construction.
- Wooden multiply sheets in single or multilayer build-up, with or without tongue and groove construction, ranging from 18 mm to 24 mm.
- On top of the wooden subfloor, a seamless Pulastic® sports floor up to 9 mm is being installed.
- A silky matt water based sealcoat finishes the floor.
- Additional line markings, logos and/or numbers on top of the sealcoat are applied, also with waterborne products.

The final result is a seamless, easy to maintain, polyurethane sports floor with truly magnificent properties.



Name	Flooring type	Nominal thickness underconstruction	Comfort	Load bearing capacity	Options toplayer
Elite Classic 70 Pure	Subfloor, wood	68 to 100+ mm	*****	**	7 mm
Elite Performance 70 Pure	Subfloor, wood	42 mm	****	*****	7 mm
Elite Performance 70 XLS	Subfloor, wood	42 mm	****	*****	7 mm
Elite Performance 90 Pure	Subfloor, wood	44 mm	*****	*****	9 mm
Elite Comfort 20 XLS	Subfloor, wood	40 mm	***	****	2 mm
Elite Comfort 70 Pure	Subfloor, wood	45 mm	*****	***	7 mm

SIKA NEDERLAND B.V.

Duurstedeweg 7 · 7418 CK Deventer · P.O. Box 420 · 7400 AK Deventer · The Netherlands
Phone: +31 570 - 62 07 44 · www.pulastic.com

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.

PULASTIC®
SPORTS FLOORING

A SIKA BRAND