

PRODUCT DATA SHEET

Regupol-6015 D2 P2P

Recycled polyurethane bonded rubber shock-pad

DESCRIPTION

Prefabricated shock-pad supplied by a company certified in conformity with ISO 9001 for quality management, ISO 14001 for environmental care, OHSAS 18001 for working conditions management, V.C.A. for safety on and according to the MVO Performance ladder, based on ISO 26000.

USES

The nature of the product requires (manufacturer) trained specialists to execute the installation.

CHARACTERISTICS / ADVANTAGES

REGUPOL 6015 D2 P2P is a durable high quality shock-pad which is mainly used for indoor sports flooring systems. We recommend that the manufacturer is consulted regarding alternative applications other than the standard sports flooring systems. The material is produced by bonding rubber crump with a polyurethane compound. The material is permanently flexible resulting in a lasting shock- and sound absorption. Further the material has a relatively high density resulting in a high hardness and a high impact resistance as well as a low standard deformation and a low remaining indentation.

PRODUCT INFORMATION

| Packaging | Thickness 12 mm | Length 18 m | Area 27 m2 | Net weight 8,7 kg/m2 | Gross weight 234 kg/rol |
|--------------------|---|----------------|---------------|-------------------------|-------------------------|
| | The width of the roll is 1.5 m | | | | |
| Shelf life | | | | | |
| Storage conditions | Store the rolls horizontally in an environment where protection against damage and free flowing water is guaranteed. Roll diameter = \pm 50 cm. | | | | |

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA NEDERLAND B.V.

Pulastic sports flooring
Duurstedeweg 7 · 7418 CK DEVENTER
P.O. Box 420
7400 AK DEVENTER · The Netherlands
Phone: +31 570 620744
www.sika.nl / www.pulastic.com

Regupol-6015D2P2P-en-NLPULA-(07-2022)-1-1.pdf

